



Boat Name _____ Skipper _____
Hull Number _____ Sail Number _____
Measurer _____ Date _____

Does this boat have a Keel/Rudder Measurement Certificate? _____

Exterior:

Starboard and Port Upper Lifelines, maximum 4" flex.
Starboard and Port Lower Lifelines do not touch deck.
Navigation Lights bow and stern?
Backstay, 10 inch maximum?
Mast - Four internal halyards (min. 3/16"/deck level adjust) with sheaves?
Mast - Chafe guard (top of mast) and Exit Plates (5)?
Mast - PVC tube?
Mast - Steaming Light and 360 deg. Masthead Light in Original Location and wired?
Mast Location - J not to exceed 13.80 feet.
Spinnaker Pole - Aluminum, aluminum pole ends. Not greater than 13 3/4 feet.
Exterior Bilge Pump in place?

Galley, Head, and Misc.:

Hatch boards?
Sink with water pump?
Ice box with pump?
Locker with doors above sink?
Stove Cover?
CNG stove with oven? Or 65 lbs.
CNG tank, regulator, & plumbing? Or 39 lbs.
CNG mounting bracket and hardware Or 6 lbs.
Chart Table with shelf above?
Marine WCHead, head door, holding tank, cleanouts, and all plumbing?
Through Hull fittings: Four, none blocked?
Builder Provided Ladder?
Cushions: Rear Quarter Berth (2), Cabin (2), Cabin Upper Berth (2),
Chart Table cushions (2), and Cabin Back Rest Cushions (4) or (6)
Forward vanity area:
a Vanity with sink, pump, cabinet or locker over (no weight)
b Half bulkhead forward of vanity (6 lb.)
c nether a or b above (26 lb.)
Locker covers (8) and mid-ship wood trim
Hull/Deck Joint wood trim

Engine System and Electrical:

Yanmar 3GM30F None
Yanmar 3GM30 18 lbs.
Yanmar 2GM20F 53 lbs.
Yanmar 2GM20 71 lbs.
Perkins M30 11 lbs.
Other TBD
Engine Box?
Martec 15" or larger
Two Group 24 batteries or equivalent? (If Not add 47 lb./batt.)
Electrical Panel with switches?

Interior lights: quarter berths (2), nav station (1), galley (1), cabin (2), vanity (1), forepeak (1) _____

Sails:

Heavy weather Jib aboard? (#3) _____

.75 oz Spinnaker aboard and is it nylon? _____

Mainsail meet requirements of Rule C.7.2? _____

Does the L1, H1, or 1/2 oz spin have class stickers? _____

Are the L1, H1, or spinnakers NEW? _____

Then: Jib 1 Weight >31 lb.: Weight _____ LP 20.63 to 21.31 ft. _____ OK? _____

Then: Jib 2 Weight >31 lb.: Weight _____ LP 20.63 to 21.31 ft. _____ OK? _____

Then: .5 Spin: max girth: 24.75 _____ Luff: max 48.3 _____ nylon _____ OK? _____

Then: .75 Spin: max girth: 24.75 _____ Luff: max 48.3 _____ nylon _____ OK? _____

Required Safety Equipment: (including USCG and PHRF Category IV per Class Rule C.5.3.j)

PFD's: One for each crew. USCG approved Type 1, 2 or 3 with whistles? _____

USCG approved Throwable Device, Type IV? _____

Tapered wood plugs? _____

Radar Reflector? _____

Flares: Min of 6 flares, USCG approved, not out of date? _____

Compass visible from the helm? _____

First Aid Kit? _____

VHF Radio? _____

Fire Ext.: 2 type B-1 or 1 type B-2 _____

Sound Producing Device: _____

Anchor Line, Minimum 150 ft. of appropriate strength? _____

Anchor Chain, Minimum 17.5 feet? _____

Anchor + chain, Min weight 26 lb. _____

I certify that the information contained in this measurement certificate is accurate. I have read the S-35 rules concerning equipment and this S-35 is in compliance with those rules.

Print Name: _____

Signed: _____